

Quilter™

the POWER of music

www.quilterlabs.com

The **BASSDOCK BD12** represents Pat Quilter's latest effort to "think inside the box". A powerful, open-back speaker solution provides a docking bay for any of our "Bass Block" or "Block Series" amplifiers, resulting in a lightweight combo with the highest available performance. The BASSDOCK BD12 can handle whatever you throw at it!

Powerful:

Best-in-class Eminence Proprietary Ferrite 12 Inch loudspeaker emphasizes your instrument's tone with a warm, smooth response, and ensures proper power handling for any gig while the included Eminence BGH25-8 super tweeter carries the upper range.

Lightweight:

Lightweight laminated construction carves away every possible ounce while providing full-size performance and tone.

Modular:

Install your choice of Bass Block or 200-Series "Block" style amp to rock the house. Use a second BASSDOCK as an extension speaker to further elevate your tone or mix and match to get a deep and punchy powerhouse!




Quick Start Guide:

Package contents:

- Qty: 1 BASSDOCK BD12
- Qty: 1 18 Gauge speaker cable
- Qty: 1 Fabric Cover

1 Remove BassDock from box:
Remove the 4 foam corners and lift the BASSDOCK free. Remove and safely discard the plastic bag covering the product. Set aside the cover and speaker cable.

2 Installing amplifier:
Keep the BASSDOCK standing. Remove the two thumb-screws from the Block retainer plate, and locate your Block amp in the foot-cups located on the internal shelf, with controls facing up.



3 Dress the speaker cable:
The speaker cable is long enough to reach an amp head sitting on top of the BASSDOCK. When docking an amp, wrap any excess cable length around the rubber feet under the amp. Leave enough slack to plug it in.



4 Plug in your block:
Plug speaker cable from Block into the speaker jack on back of BASSDOCK.



BASS DOCK BD 12

5 Replace retainer plate:
Align the oval holes in the BASSDOCK retainer plate with the threaded inserts in the cabinet. Replace both thumb-screws, being careful not to cross-thread them. Amp should now be firmly retained with the controls just below the top surface for protection.



6 Using the BASSDOCK BD12:
The assembled BASSDOCK combo competes with bass rigs up to twice its size and weight. The rear mounted port contributes to the lowest octave and should be kept several inches away from any obstruction. The cabinet may be tilted back with a wedge or stand, but lifting it off the floor will weaken low frequency coupling. Consult the amplifier's instruction manual for tips on control adjustments and optimum use.

7 Using the provided cover:
When transporting or not in use, keep the cover on the cabinet to prevent dust buildup and protect from damage.



Troubleshooting:

Symptom	Check
No sound	Ensure that all cables are fully inserted and plug a known-good guitar straight into the amp. Confirm the amp power LED is on. Try another speaker to confirm the amp is working, or try another amp to confirm the speaker is functioning correctly. If the amp or speaker produce no sound using these tests, contact Quilter Labs for replacement instructions.
Speaker "flaps", buzzes, pops, or sounds garbled at all levels	The speaker may be damaged or worn out. Try another speaker to confirm the amp is normal. Contact Quilter Labs for replacement instructions.
Sound is intermittent. "scratchy", or hums.	Look for loose connections at every point in the chain including the pedal board. Gently move each cable listening for changes in the signal. Try another speaker to check if the internal speaker is bad. If so, contact Quilter Labs for replacement instructions.

**For USA warranty information visit us online at www.quilterlabs.com.
Outside the USA please contact your Quilter dealer for further information but visit us on the web anyway!**

Quilter Part Number: 001133 Rev A