

Quilter™

Performance Amplification

The BLOCKDOCK 10TC represents Pat Quilter's latest effort to "think inside the box". A compact closed-back speaker solution provides a docking bay for any of our "101 Mini Series" amplifiers, resulting in a light-weight combo with amazing performance. The BLOCKDOCK 10TC can handle whatever you throw at it!

Powerful:

Pro-audio-grade 10-inch loudspeaker eliminates cone cry, emphasizes your instrument's tone with a full-bodied, crisp response, and ensures proper power handling for any gig.

Compact and versatile:

The 10-inch speaker and lightweight laminated construction carve away every possible ounce while providing full-size performance and tone. The tilt-back cabinet shape provides two listening angles for easy monitoring.

Modular:

Install your choice of 101-Series "Block" style amps to rock the house. Use a second BLOCKDOCK as an extension speaker to further elevate your tone! NOTE: a Block-200 series amp will also fit, but should only be used at 50% Master, or with an extension speaker to handle the extra power.



Quick Start Guide:

Package contents:

Qty: 1 BlockDock 10TC

Qty: 1 18 Guage speaker cable

Qty: 1 Fabric Cover

- 1** Remove BlockDock from box: Remove the 4 foam corners and lift the BLOCKDOCK free.

Remove and safely discard the plastic bag covering the product. Set aside the cover and speaker cable.

- 2** Installing amplifier: Lay BLOCKDOCK face down. Remove the two thumb-screws from the Block retainer plate, and locate your Block amp in the foot-cups located on the internal shelf, with controls facing up.



- 3** Dress the speaker cable: The speaker cable is long enough to reach an amp head sitting on top of the BLOCKDOCK. When docking an amp, wrap any excess cable length around the rubber feet under the amp. Leave enough slack to plug it in.



- 4** Plug your block in: Plug speaker cable from Block into the speaker jack on back of BLOCKDOCK. Plug in AC power cable.



BLOCKDOCK^{TC} 10

5 Replace retainer plate: Align the oval holes in the BLOCKDOCK retainer plate with the threaded inserts in the cabinet. Replace both thumb-screws, being careful not to cross-thread them. Amp should now be firmly retained with the controls just below the top surface for protection.



6 Using the BLOCKDOCK 10TC The assembled BLOCKDOCK provides best-in-class power and tone with minimal weight. The closed back optimizes bass response and projects the sound forward, making full use of the 101 Series power output. The cabinet may be tilted back for better audibility. Consult the amplifier's instruction manual for tips on control adjustments and optimum use.

7 Using the provided cover: When transporting or not in use, keep the cover on the cabinet to prevent dust buildup and protect from damage.



Troubleshooting:

Symptom	Check
No sound	Ensure that all cables are fully inserted and plug a known-good guitar straight into the amp. Confirm the amp power LED is on. Try another speaker to confirm the amp is working, and try another amp to confirm the speaker works. If the amp or speaker produce no sound using these tests, contact Quilter Labs for replacement instructions.
Speaker "flaps", buzzes, pops, or sounds garbled at all levels	The speaker may be damaged or worn out. Try another speaker to confirm the amp is normal. Contact Quilter Labs for replacement instructions.
Sound is intermittent. "scratchy", or hums.	Look for loose connections at every point in the chain including the pedal board. Gently move each cable listening for changes in the signal. Try another speaker to check if the internal speaker is bad. If so, contact Quilter Labs for replacement instructions.

For USA warranty information visit us online at www.quilterlabs.com. Outside the USA please contact your Quilter dealer for further information but visit us on the web anyway!